

Top-loading expanded polypropylene insulated container 60x40 cm

406902

PRODUCT SHEET



Material(s):

Ppe (expanded polyst.)

Country of origin:

ITALY

Customs number:

3924100000



PRODUCT DESCRIPTION

- ✓ Polypropylene is expanded with CO₂, it is CFC- and HCFC-free, and has no residual expansion agents
- ✓ Designed to protect hot or cold food from thermal shock
- ✓ Ideal for transporting 600x400 mm baking trays or containers
- ✓ Average temperature drop of 1.5 °C per hour
- ✓ Top opening
- ✓ Compliant with standard UNI EN 12571
- ✓ 100% recyclable

SALES DATA

Sales unit:

1

MOQ:

1

PRODUCT FEATURES

Dimensions Commercial Variant

	Commercial version CV 1	Commercial version CV -1	Commercial version CV -2
<u>Designation</u>	Top-loading expanded polypropylene insulated container 60x40 cm		
Contains		VC-1	VC-2
Height	31 cm		
Total Length	68,5 cm		
Width	42,5 cm		
Volume	90,2 dm ³		
Net weight	1,34 kg		
Gross weight			
Bar code	3760245470323		

Top-loading expanded polypropylene insulated container 60x40 cm

406902

PRODUCT FEATURES

Product dimensions		Guarantee	
Useful length	54 cm	Guarantee term	24 mois
Useful capacity	82,3 L	Regulatory	
Material		CE marking	yes
Main material	Ppe (expanded polyst.)	Environmental impact	
Material thickness	30 mm	Is the product recyclable?	yes
Is the material recyclable?	yes with 100 %	Color & Finish	
Color & Finish		UFI number	N
Colour	NOIR	Use conditions	
Use conditions		Minimum operating temperature	-40 °C
Minimum operating temperature	-40 °C	Maximum operating temperature	120 °C
Maximum operating temperature	120 °C		

LOGISTICS DATA

Quantity	UNIT		SUB-CONDITIONING		MASTER		PALLET	
			contains:		contains:		contains:	
					1	underpacking	12	masters
					1	unit(s)	4	layers
							3	masters / layer
							12	unit(s)
Weight	1,410	Net in kg		Net in kg	1,4	Net in kg	17	Net in kg
	1,410	Gross in kg		Gross in kg	1,4	Gross in kg	17	Gross in kg
	0,000	Net packing in kg		Net packing in kg	0,0	Net packing in kg	0	Net packing in kg
Dimensions	38,000	H in cm		H in cm	38,0	H in cm	210	H in cm
	49,000	W in cm		W in cm	49,0	W in cm	80	W in cm
	69,000	L in cm		L in cm	69,0	L in cm	120	L in cm
	128,470	V in dm³		V in dm³	128,5	V in dm³	2016	V in dm³
Bar code	type	EAN	type	EAN	type	EAN	type	EAN
	CTM	406902						