

822508

PRODUCT SHEET



Material(s):

Ppe (expanded polyst.)

Country of origin:

ITALY

Customs number:

3924100000



PRODUCT DESCRIPTION

- ✓ Polypropylene is expanded with CO₂, it is CFC- and HCFC-free, and has no residual expansion agents
- ✓ Designed to carry food and keep it warm
- ✓ Can be closed or opened even when stacked
- ✓ Easy front opening with fully removable door
- ✓ Easy to handle lightweight container
- ✓ Average temperature drop of 1.5°C per hour
- ✓ Compliant with standard UNI EN 12572
- ✓ Compliant with HACCP
- ✓ 100% recyclable
- ✓ Includes 9 shelves spaced 50 mm

SALES DATA

Sales unit:

1

MOQ:

1

PRODUCT FEATURES

Dimensions Commercial Variant

	Commercial version CV 1	Commercial version CV -1	Commercial version CV -2
<u>Designation</u>			
Contains		VC-1	VC-2
Height	61 cm		
Total Length	65 cm		
Width	50 cm		
Volume	198,2 dm ³		
Net weight	6,4 kg		
Gross weight			
Bar code	3760245471894		

822508

PRODUCT FEATURES

Product dimensions		Use conditions	
Useful lenght	53 cm	Minimum operating temperature	-40 °C
Space between runners	50 mm	Maximum operating temperature	120 °C
Entry width	32,5 cm	Guarantee	
Material		Guarantee term	24 mois
Main material	Ppe (expanded polyst.)	Regulatory	
Material thickness	50 mm	CE marking	yes
Color & Finish		Environmental impact	
Colour	NOIR	Is the product recyclable?	yes
Electric			
Power	170 W		
Voltage	220-240 V		
Electrical material frequency	50 Hz		

LOGISTICS DATA

Quantity	UNIT		SUB-CONDITIONING		MASTER		PALLET	
			contains:		contains:	1 underpacking	contains:	6 masters
					contains:	1 unit(s)	contains:	3 layers
							contains:	2 masters / layer
							contains:	6 unit(s)
Weight	6,490	Net in kg		Net in kg	6,5	Net in kg	39	Net in kg
	6,490	Gross in kg		Gross in kg	6,5	Gross in kg	39	Gross in kg
	0,000	Net packing in kg		Net packing in kg	0,0	Net packing in kg	0	Net packing in kg
Dimensions	66,000	H in cm		H in cm	66,0	H in cm	162	H in cm
	50,000	W in cm		W in cm	50,0	W in cm	80	W in cm
	60,000	L in cm		L in cm	60,0	L in cm	120	L in cm
	198,000	V in dm³		V in dm³	198,0	V in dm³	1555	V in dm³
Bar code	type	EAN	type	EAN	type	EAN	type	EAN
	CTM	822508						